

# Badger

Fire Protection

## Regular Dry Chemical



Badger's regular dry chemical stored pressure fire extinguishers are specifically designed to meet the needs of industrial and commercial premises where there is a flammable liquid risk. They are cost effective to maintain and offer good value and excellent performance.

They are available in two versions, Badger*Extra* our premium line and, Badger*Standard* our value line.

Suitable for use on class B and C fires they mount on any surface with wall hook or if preferred, can be supplied with optional vehicle bracket.

### Features - Badger*Extra*

- Available in four sizes, 2¾ lb, 5½ lb, 10 lb & 20 lb
- Chrome plated brass valves
- Stainless steel handle, lever and hose band
- Color coded labels for instant type recognition
- Re-designed label incorporating easy to follow instructions and larger fire pictograms
- Operate effectively at both high and low temperatures.
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- 12 year interval between hydrotests
- USCG approved

### Features - Badger*Standard*

- Available in two sizes, 5½ lb & 10 lb
- Aluminum valve, handle, lever and pull pin
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- Operate effectively at both high and low temperatures
- 12 year interval between hydrotests
- USCG approved

UL listed  
Six year warranty



Badger*Extra*



Badger*Standard*

Badger*Extra*  
 Models:  
 B275BC  
 B5BC  
 B10BC  
 B20BC

Badger*Standard*  
 Models:  
 5RB-4H  
 10RB-7H

## Specifications

Specifications	Badger <i>Extra</i>				Badger <i>Standard</i>	
	B275BC	B5BC	B10BC	B20BC	5RB-4H	10RB-7H
Model Number	B275BC	B5BC	B10BC	B20BC	5RB-4H	10RB-7H
Nominal Capacity (lbs)	2.75	5.5	10	20	5.5	10
Nominal Capacity (kilograms)	1.25	2.49	4.54	9.07	2.49	4.54
UL Fire Rating	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C
Agent Type	BC	BC	BC	BC	BC	BC
Item Part Number	23471	23476	23781	23482	22478	22676
Valve Material	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Aluminum	Aluminum
Shell Material	Steel	Steel	Steel	Steel	Steel	Steel
Shipping weight (lbs)	5.4	10.4	18.0	33	10	17
Shipping weight (kilograms)	2.11	4.7	8.16	15	4.5	7.7
Operating Pressure	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI
Temperature Range (°F)	-40° to 120°	-40° to 120°	-40° to 120°	-40° to 120°	-40° to 120°	-40° to 120°
Discharge Time (seconds)	9.0	13.5	18.0	29.0	13.5	18
Discharge Range (feet)	10-15	12-18	16-20	16-20	12 to 18	16 to 20
Discharge Range (meters)	3.14-4.6	3.7-5.5	4.9-6.1	4.9-6.1	3.7 to 5.5	4.9 to 6.1
Unit Height (inches)	14.875	15.25	19.15	21.13	15.25	18.94
Unit Height (centimeters)	37.7	38.7	48.59	53.67	38.7	48.1
Unit Width (inches)	5.50	7.25	8.13	9.25	7.25	7.75
Unit Width (centimeters)	13.9	14.7	20.65	23.49	18.41	19.68
Shell Diameter (inches)	3	4.25	5.25	7.25	4.25	5.25
Shell Diameter (centimeters)	7.62	10.8	13.33	18.41	10.48	13.33
USCG Approval	Yes	Yes	Yes	Yes	Yes	Yes
USCG Bracket	MB-250	MB-5	UB-10	UB-20	MB-5	UB-10
	Included	Optional	Optional	Optional	Optional	Optional

BFPN0002

**Badger**

Fire Protection

4251 Seminole Trail  
 Charlottesville, VA 22911  
 Tel. (800) 446-3857  
 Fax. (800) 248-7809  
[www.badgerfire.com](http://www.badgerfire.com)